


5-Lobe Pin



5-Lobe Pin - Countersunk Head Self Tapping Screws - A4-70 Stainless Steel



Dimensions (mm)

SCREW TYPE 5-LOBE PIN	METRIC MACHINE SCREWS			
	DIMENSIONS	6g	8g	10g
COUNTERSUNK HEAD		6.8	8.1	9.5
		I 3.0	3.4	3.8

Material and Finish

Material: A4-70 Minimum Tensile Strength 700N/mm²
Heat Treatment: None
Finish: Passivated

Size & Part Numbers

GAUGE	LENGTH	1/2"	3/4"	1"	1 1/2"	2"	DRIVER SIZE
		13mm	19mm	25mm	38mm	50mm	
6	3.5mm	FLPCS06D-A4	FLPCS06F-A4	FLPCS06G-A4			T15
8	4.2mm		FLPCS08F-A4	FLPCS08G-A4	FLPCS08I-A4	FLPCS08J-A4	T20
10	4.8mm		FLPCS10F-A4	FLPCS10G-A4	FLPCS10I-A4	FLPCS10J-A4	T25

Additional Information

Patented Product: Hafren Fasteners
Installation: 5-Lobe Pin - see video
Removal: 2-Way Removable Screw

- ✓ High torque drive
- ✓ 5-Lobe with Pin design
- ✓ A4-70 Stainless Steel
- ✓ Button and Countersunk Head
- ✓ Metric Machine Screws and Self Tapping Screws

Every effort has been made to ensure the accuracy of information provided in this catalogue. Hafren Fasteners cannot warrant the information however, expressly or implied, and any liability arising from it is expressly excluded. Customers must satisfy themselves as to the suitability of products and the technical information relating to them, and it is recommended that you conduct your own tests to establish suitability. All sizes shown are in mm without min and max tolerances and are guide sizes. Hafren Fasteners reserve the right to change/alter sizes without notice. This does not effect your statutory rights.